

Braiding Machine SE 266

with 12, 16, 20, 24, 32 Carriers

For ropes between 6 and 50mm



HERZOG[®]
Braiding machines

CLEVER SOLUTIONS SINCE 1861



August Herzog Maschinenfabrik GmbH & Co. KG
Am Alexanderhaus 160, D-26127 Oldenburg
Telefon: +49/ 441/3008-0 Fax.: +49/441/3008-100
www.herzog-online.com

Technical Data
Rope Braiding Machine SE 266



HERZOG®
Braiding machines

CLEVER SOLUTIONS SINCE 1861

with 12 / 16 / 20 / 24 or 32 carriers,
for Ropes between 6 – up to 50mm
diameter

With proven supported HERZOG carrier guiding system.
All horn gears and intermediate gears are running on
special needle ball bearings.

Main and take-off drive running in oil-bath. All bearings laying bare are free of
attendance by continuous greasing. By this HERZOG conception:
extremely quiet in operation, extremely easy to attend, extremely safe in
operation, designed for continuous operation for years.

Single-head design, with capston 500 or 700 mm diameter,
width 110 or 200 mm.

Driving aggregate: electric motor with all necessary
control devices, incl. electronic control against
motor overload and electrically controlled reverse
motion. Indication of machine stop by means of signal
lamp. Convenience outlet 230 V.
Voltage: 400 V / 50 cycles / 3f + N

Underframe of stable steel construction.
Colour: turquoise RAL 5018

Equipped with HERZOG special carrier AFZP 266 with shoe brake
mechanism.

This construction guarantees an absolute exact brake, extremely quiet in
operation.

The brake shoes - mounted inside and protected against
dust - are made of wear-resisting material which is
free of Asbestos. The yarn tension can be adjusted
by means of easily exchangeable tension spring being
mounted at the outer side.

This carrier is suitable for any kind of yarn, either made of natural or man-
made fibers.

Suitable for HERZOG braiding bobbins, Alu-plastic,
135 mm x 380 mm = 5.074 ccm volume.

Speed: 110 horn gear r. p. m.