

HSM 550

Ropemaking machine for production of Hercules ropes



Machine design

For processing of most natural and man-made fibres <ul style="list-style-type: none"> • With wire insert 	For production of 3, 4 or 6-stranded ropes up to Ø 40 mm	For strands with diameter 3 – 15 mm
Rotor with 6 wings	Wing with drum take-up <ul style="list-style-type: none"> • Drum Ø 550 x 235 mm • Take-up via drum axis • Brake unit adjustable via spring loaded belt • 2 take-in capstans Ø 300 x 60 mm 	Large clutch to adjust the tension of the 6 strands
6 preforming units	Knot detector with splittable insert	Postforming unit after knot detector
Full protection covering <ul style="list-style-type: none"> • Sheet metal cladding with window 	Take-off via <ul style="list-style-type: none"> • 2 x take-off disc Ø 850 x 260 mm • 5 grooves with U profile 	Control via graphic touch panel <ul style="list-style-type: none"> • Integrated product data management • Electronic lay length control • Rotor speed adjustment • Meter counter and work hour counter • Fault cause to be shown on display

Herzog GmbH

Am Alexanderhaus 160 · D-26127 Oldenburg
 T: +49 (0) 4 41 / 30 08 - 0 · F: +49 (0) 4 41 / 30 08 - 100
info@herzog-online.com · www.herzog-online.com

